

ERRATUM / ERRATUM

Erratum: Combined effects of reinforcement and prefabricated vertical drains on embankment performance**Allen Lunzhu Li and R. Kerry Rowe**

Ref.: Can. Geotech. J. **38**: 1266–1282 (2001).

The hydraulic conductivity change index, C_k , reported in Table 1 (Soil model parameters) of the above paper, should have been 1.25 for soils A and B, respectively.

In Appendix: A worked sample of the above paper and step (6), the back-calculated $t_{O/C}$ should be 624 h instead of 186 h. Using eqs. [9] and [10] and $C_{N/C}$, the calculated $\bar{U}_{N/C}$ is 5.8% at $t = 9$ months, which should be at $t = 810$ h at EOC. Using eq. [8], the calculated \bar{U}_f should be 42.1% instead of 42.5%. For step (7): the \bar{U}_f value of 0.425 should be 0.421 and the calculated Δs_{uf} value should be 2.57.

Received 26 May 2004. Accepted 26 May 2004. Published on the NRC Research Press Web site at <http://cgj.nrc.ca> on 2 July 2004.

A.L. Li and R.K. Rowe.¹ Department of Civil Engineering, Ellis Hall, Queen's University, Kingston, ON K7L 3N6, Canada.

¹Corresponding author (e-mail: kerry@civil.queensu.ca).

